



Catalog # GMC-080209

Hydraulic Notcher

Model # HN-08HA
Model # HN-25HA
with 90° fixed angle

ISO 9001



Standard Features:

- ISO 9001 certified
- Super large table
- All steel construction
- Safety finger guards
- (2) quick change gauges
- Foot pedal control
- Quiet hydraulic system
- One year warranty

Specifications	GMC HN-08HA	GMC HN-25HA
Max. capacity: mild steel (C.R.S.)	8 Ga.	1/4"
Max. capacity: stainless steel	12 Ga.	3/16"
Min. notching thickness	26 Ga.	22 Ga.
Notching angle , fixed angle	90 degree	90 degree
Max. cutting length	10"	10"
Stroke per minute	12	12
Table dimensions, L x W	32" x 26"	32" x 26"
Hydraulic oil tank capacity	12 Gal.	15 Gal.
Main motor	5 1/2 HP, 220V, 3-phase	7 1/2 HP, 220V
Machine weight	1,850 LBS	2,650 LBS
Machine dimensions, L x W x H	37" x 35" x 48"	40" x 36" x 50"

Specifications are subject to change without prior notice

Distributor:

Distributor:



Catalog # GMC-080209

Hydraulic Notcher

Model # HN-08HB with variable angle

ISO 9001



Standard Features:

- ISO 9001 certified
- 5½HP HD motor
- Super large table
- All steel construction
- Safety finger guards
- (2) quick change gauges
- Foot pedal control
- Quiet hydraulic system
- One year warranty

Specifications	GMC HN-08HB
Max. capacity: mild steel (C.R.S.)	8 Ga.
Max. capacity: stainless steel	12 Ga.
Min. notching thickness	26 Ga.
Notching angle, variable	40 to 130 degree
Max. cutting length	7-3/4"
Stroke per minute	18
Table dimensions, L x W	40" x 38"
Hydraulic oil tank capacity	12 Gal.
Main motor	5½ HP, 220V, 3-phase
Machine weight	2,650 LBS
Machine dimensions, L x W x H	67" x 38" x 56"

Specifications are subject to change without prior notice

Distributor:

Distributor: