



Catalog # GMC-033011

# Pittsburgh Type Locking Former Model # PL-20E

ISO 9001



### Standard Features:

- ISO9001 certified
- 1.5HP Heavy Duty AC main motor,110V
- Heavy welded all steel construction
- Standard Pittsburgh Attachment
- Standard Round Flange Attachment  
Double Seam Roll and Drive cleat Roll
- ACME side can be operated at same time
- Heavy Duty caster wheels for easy moving
- One year warranty for parts



FA-20E

STANDARD  
LOCK FORMED IN BOARD



PA-20E:

FA-20E:



DCR-20E:



DSR-20E:



RAR-20E:



### Standard Equipment:

- Standard Pittsburgh Attachment # PA-20E
- Flange attachment # FA-20E,installed
- Drive cleat roll # DCR-20E,installed
- Double seam roll # DSR-20E

Specifications	Model# PL-20E
Capacity:	20Ga.to 26 Ga
Depth of pocket	5/16"
Feeding speed	32FPM
Main motor	1.5 HP, 110V
Weight approx	458 LBS
Machine dimensions L x W x H	36" x 23" x 43"

\* All specifications and design are subject to change without prior notice



Catalog # GMC-033011

# Pittsburgh Type Heavy Duty Locking Former # PL-16E

ISO 9001



### Standard Features:

- ISO9001 certified
- 5-1/2 HD AC main motor
- Heavy welded all steel construction
- Standard Pittsburgh Attachment
- Standard Round Flange Attachment  
Double Seam Roll and Drive cleat Roll
- ACME side can be operated same time
- One year warranty for parts



FA-16E

STANDARD  
LOCK FORMED IN BOARD



PA-16E:

FA-16E:



DCR-16E:



DSR-16E:



RAR-16E:



### Standard Equipment:

- Standard Pittsburgh Attachment
- Flange attachment # FA-16E
- Drive cleat roll # DCR-16E
- Double seam roll # DSR-16E

Specifications	Model# PL-16E
Capacity:	16 Ga.to 20 Ga
Depth of pocket	1/2"
Feeding speed	23PM
Main motor	3HP, 220V,3PH
Weight approx	628 LBS
Machine dimensions L x W x H	43" x 27" x 48"

\* All specifications and design are subject to change without prior notice