



Catalog # GMC-032708

HYDRAULIC SHEARS

ISO 9001



HS-0410MD

Standard Features:

- ISO 9001 certified
- HD all steel construction for maximum rigidity
- German logic quiet hydraulic system
- Spring hold-downs
- high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 4-edge indexable bottom blade
- Full length with full view finger guard
- Front supports and (2) side gauges
- Safety type foot pedal control
- Jog, single or auto cycle operation modes



HYDRAULIC SHEARS

HS-0410MD

ISO 9001

Cutting capacity:	HS-0410MD	HS-0414M	HS-0510M	HS-0610M	HS-0810M	HS-1010MD
mild steel	53" x 10Ga.	53" x 14 Ga.	62" x 10 Ga.	82" x 10 Ga.	101" x 10 Ga.	123" x 10Ga.
stainless steel	53" x 14 Ga.	53" x 18 Ga.	62" x 14 Ga.	82" x 14 Ga.	101" x 14 Ga.	123" x 14 Ga.
Blade length	53"	52"	62"	82"	101"	123"
Strokes per minute	37	37	30	25	20	16
Hold-downs:	8 pcs	8 pcs	9 pcs	10 pcs	12 pcs	16 pcs
Front support length	24"	24"	24"	24"	24"	24"
Manual back gauge	24"	24"	24"	24"	24"	24"
Top blade rake angle	1.5 degree	1.5 degree	1.5 degree	1.5 degree	1.5 degree	1.5 degree
Hydraulic oil tank	20 Ga.	17 Gal.	20 Gal	25 Gal.	25 Gal.	30 Gal.
Main motor	5HP, 220V	3 HP, 220V	5 HP, 220V	5 HP, 200V	5 HP, 220V	7-1/2 HP, 220V
Machine weight	3,150 LBS	1,950 LBS	3,850 LBS	4,350 LBS	6,050 LBS	6,650 LBS
Dimensions, approx.	80x38x58"	80x38x57"	88x39x58"	110x39x58"	136x39x58"	160x39x58"

* Design and specifications are subject to change without prior notice

Standard Equipment:

1. 24" one-side handwheel operated manual back gauge
2. 2 each 24" front support arms
3. 2 each 14" Side gauges with inlaid inch/metric scale
4. Removable safety foot pedal control
5. One set of blades
6. Full length finger guard
7. Tool box with tools
8. Spring hold-downs

Distributor:

Distributor: